

Full HD Network Camera



- Super clear full-HD 2 mega pixel resolution
- 2DNR (2Dimensional Noise Reduction)
- Extremely low light performance true Day/Night with IR cut filter
- Universal OnVIF supported CODEC
- Extreme back Light compensation performance
- Two-way audio
- Micro SD supported
- Multiple compression (H.264, MPEG4, MJPEG)
- Dual IP streaming
- Cross web-browsing
- Motion adaptive transmission
- Dynamic adjustment bit rate
- Event buffering
- FTP image upload capability
- Web casting
- Password protection, IP filtering
- DC12V, PoE



Get the free mobile app for your phone
<http://gettag.mobi>

Costar Video Website



Full HD Network Camera Specifications

Model

CCIH200	Full HD box camera, iNEX, 2 mega pixel, dual streaming, DC12V, PoE
---------	--

Imaging

Image Sensor	1/2.7" CMOS
Lens	Megapixel C/CS Mount
Scanning Mode	Progressive Scan
Min. Illumination	Color: 2.5Lux, B/W: 0.2Lux (F1.2, 50IRE)
AE/AWB	Yes
DNR	2DNR
Day/Night	True Day/Night (IR-cut filter)
WDR	No
DIS	No
BLC	BLC

VIDEO

Video Out	Yes (Max D1 for installation)
Progressive Encoding	Yes
Compression	H.264(BP/MP/HP), MPEG4(ASP/SP), MJPEG
Resolution Supported	1080p, 1280x1024, 720p, D1, Half-D1, VGA, QVGA, CIF
Frame Rate	30fps @ H.264 1080p + 5fps @ MJPEG QVGA, 25fps @ H.264 1080p + 30fps @ MJPEG VGA 30fps @ H.264 720p + 30fps @ MJPEG 720p
Multiple Streaming	Dual

Feature

Motion Detection	Yes
Event Buffering (Pre & Post)	Yes(up to 64MB)
Privacy Masking	Yes (8 windows)
Pre-recorded Voice Alert	Yes (up to 3 files)
Video Analytics	No
Cross Web Browser	Safari, Firefox, Google Chrome
FTP Image Upload	Yes
ONVIF Certificate	Yes

System

Network Time Sync	Yes
Zero Configuration	Yes
Security	Password Protection, IP Filtering, HTTPS, SSL

NETWORK

Max. Connections	10
Protocols	IPv4/IPv6, Manual, TCP/IP,UDP,HTTP,RTP,RTSP, NTP,DHCP,SMTP,DDNS,HTTPS ,RTCP,FTP,Bonjour
NAS Support	Yes
JPEG push	Yes
DDNS	Yes (DDNS)
Remote Client	iNEX

IN/OUT

Audio In/Out	In x 1/ Out x 1 (G.711)
Alarm In/Out	In x 1 /Out x 1
RS485	Yes
Ethernet	10/100Mbps
Local Storage	Micro SD

Miscellaneous

Weatherproof	No
PoE	802.3af Class 2
Power	DC12V, PoE
Power Consumption	Max. 3.5W
Operating Temperature	0 ~ 50°C
Humidity	0~90% RH
External Dimension	2.67"H x 3.21"W x 4.84"D(68H x 81.6Wx123.1Dmm)

Applications



iNEX

Connect to the future with Legacy connection from DVRs, and IP servers

Dimensions (mm)



Costar
VIDEO SYSTEMS

101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6800 • Fax: 469-635-6822 • Toll Free: 1-888-694-STAR (7827)

www.costarvideo.com